

**PATENT APPLICATION**

5

**OF**

**LARRY MYLAND**

**FOR**

**PARTICLE BARRIER DRAIN**

15

Prepared by:

20 Michael B. Fein  
Cozen and O'Connor  
1900 Market Street  
Philadelphia, PA 19103  
215-665-4622  
fax: 215-701-2246

PHILA1\1533894\2 108430.000

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of Provisional Application No. 60/257,562 filed December 22, 2000.

## BACKGROUND OF THE INVENTION

### 5 1. Field of the Invention

The present invention relates to the fabrication of integrated circuits, and more particularly to an apparatus and process that facilitates the uniform overflow of a liquid containing contaminants from a process tank and prevents the contaminated liquid from reentering the process.

### 10 2. Description of the Prior Art

Integrated circuit devices are produced on semiconductor wafers where each wafer can produce a multitude of integrated circuit devices. The exact number of devices that can be produced on any single wafer depends both on the size of the wafer and the size of the devices being produced thereon. In the production of integrated circuit devices, the importance of minimizing the amount of contaminants on the wafers at all stages of processing has long been recognized in the industry. Contaminants cause otherwise properly processed devices to not function properly upon completion of the production process. As a result of this contamination, the yield of properly functioning devices obtained from any given wafer decreases.

Moreover, cleanliness requirements have become increasingly important as a result of  
20 the devices becoming more and more miniaturized. When dealing with reduced size devices, the ratio of the size of a contaminant compared to the size of a device is greater, resulting in an increased likelihood that a contaminated device will not function properly. Thus, increasingly stringent cleanliness requirements are needed. As a result, improved semiconductor wafer

processing techniques that reduce the amount and size of the contaminants present during wafer production are highly desired.

One method used to clean wafers that is known in the art is overflow. In overflow washers, wafers are cleaned by supplying a rinsing liquid through the bottom of a tank in which the wafers are located. The liquid is continuously supplied so that the liquid eventually fills the tank and overflows its sides. The theory behind the cleaning function of overflow washers is that as the tank fills with fresh, clean liquid, the dirtier liquid that contains contaminants that have been removed from the wafers is removed from the upper portion of the tank by overflow, the dirty liquid being continuously replaced with fresh, clean liquid. Additionally, many overflow washers also include a bubbler which introduces a stream of nitrogen bubbles into the bottom of the tank to enhance the rinsing action of the flowing liquid and which helps carry contaminants to the surface of the liquid where they will be removed from the tank by the overflowing liquid. Another technique utilized in the art to increase the cleanliness of the liquid used in overflow washers is to facilitate uniform overflow of the liquid from the tank. Uniform overflow is accomplished in the art by providing a multitude of peaks at or near the top of the tank walls, these peaks in turn forming a corresponding recess between each pair of peaks. The surface liquid overflows the tank walls through such recesses, causing the liquid to overflow the tank walls from all sides and thus facilitating a uniform overflow of surface liquid from the tank. Because a uniform overflow of liquid more effectively removes contaminants located on or near the surface of the liquid than a non-uniform overflow of liquid, the liquid remaining in the tank contains less contaminant and is cleaner.

While employing recesses does facilitate uniform overflow, the surface liquid overflows the tank walls only through the recesses. This results in a small area of surface fluid maintaining a steady state (i.e. a zero flow rate) at each peak of the tank walls. This lack of flow near the

peaks of the tank walls results in contaminants that are present in the surface tension of the liquid adhering to the peaks of the tank walls. As the surface liquid continues to overflow the tank through the recesses, a significant amount of contaminants can build up at the peaks. When the supply of liquid to the tank is stopped and the remaining liquid is drained from the tank, some of these contaminants will migrate back over the surface of the liquid. As the surface level of the liquid lowers past the wafers, some of these contaminants often come back into contact with the cleaned wafers, resulting in re-contamination of the wafers and an increase in the number of devices that will not function properly.

Thus, there is a need for a system that can facilitate the uniform overflow of liquid from a tank without allowing contaminants to reenter that area of the tank in which the wafers are located.

### SUMMARY OF THE INVENTION

These needs and others are met by the present invention which comprises in one aspect a system that facilitates the uniform overflow of liquid from a process tank while preventing contaminants from reentering the process tank upon draining the process tank. The system comprises an inner weir having a top surface; an overflow wall having a top with at least one recess, the at least one recess having a bottom; wherein the top surface of the inner weir is below the bottom of the at least one recess; and a structure connecting the overflow wall and the inner weir so as to form a drainage basin, the drainage basin having at least one drain hole.

Preferably, the top surface of the inner weir has an inside edge and an outside edge, the top surface of the inner weir being tapered downwardly from the inside edge to the outside edge, wherein the inside edge of the top surface is below the bottom of the at least one recess. The at least one recess can be saw-toothed, rectangular, or semi-circular.

Optionally, the system also comprises a drain valve that is fluidly connected to the at least one drain hole. The drain valve has an open and closed position so that the at least one drain hole is hermetically sealed when the drain valve is closed and allows fluid to freely flow through the at least one drain hole when the drain valve is opened.

5 In the preferred embodiment, the system of invention comprises an inner weir having a top surface; an overflow wall having a top with at least one recess, the at least one recess having a bottom; wherein the top surface of the inner weir is below the bottom of the at least one recess; and a structure connecting the overflow wall and the inner weir so as to form a drainage basin, the drainage basin having at least one drain hole; a drain valve fluidly connected to the at least one drain hole, the drain valve having an open and closed position so that the at least one drain hole is hermetically sealed when the drain valve is closed and allows fluid to freely flow through the at least one drain hole when the drain valve is opened; wherein the top surface of the inner weir has an inside edge and an outside edge, the top surface of the inner weir being tapered downwardly from the inside edge to the outside edge, wherein the inside edge of the top surface is below the bottom of the at least one recess; and wherein the at least one recess is saw-toothed.

In another embodiment, the invention is a process tank comprising the system of invention described above. The process tank can be a rinsing tank, a drying tank, or a chemical treatment tank.

10 In even another embodiment, the invention is a method of facilitating uniform overflow of liquid from a process tank while preventing contaminants from reentering the process tank upon draining the process tank. The method comprises the steps of: providing a process tank comprising the system of invention described above; supplying a liquid to the process tank wherein the liquid comprising contaminants overflows the inner weir, fills the drainage basin, and overflows the overflow wall through the at least one recess of the overflow wall; and

wherein upon discontinuing the supply of liquid to the process tank, the contaminants do not reenter the process tank.

Optionally, the at least one drain hole used in this method is fluidly connected to a drain valve having an open and closed position so that the at least one drain hole is hermetically sealed when the drain valve is closed and allows fluid to freely flow through the at least one drain hole when the drain valve is opened.

Preferably, in performing the method above, the drain valve is opened essentially in concurrence with discontinuing the supply of liquid to the process tank.

The top surface of the inner weir can have an inside edge and an outside edge, wherein the top surface of the inner weir is tapered downwardly from the inside edge to the outside edge, wherein the inside edge of the top surface is below the bottom of the at least one recess. Also, the at least one recess can be saw-toothed, rectangular, or semi-circular.

In the preferred embodiment, the method of invention comprises providing a process tank comprising the system of invention described above; supplying a liquid to the process tank wherein the liquid comprising contaminants overflows the inner weir, fills the drainage basin, and overflows the overflow wall through the at least one recess of the overflow wall; and wherein upon discontinuing the supply of liquid to the process tank, the contaminants do not reenter the process tank; wherein the at least one drain hole is fluidly connected to a drain valve having an open and closed position so that the at least one drain hole is hermetically sealed when the drain valve is closed and allows fluid to freely flow through the at least one drain hole when the drain valve is opened; wherein the top surface of the inner weir has an inside edge and an outside edge, the top surface of the inner weir being tapered downwardly from the inside edge to the outside edge, wherein the inside edge of the top surface is below the bottom of the at least one recess; and wherein the at least one recess is saw toothed.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an elevational view of a square process tank implementing the system of the present invention.

FIG. 2 is a top view of the square process tank implementing the system of the present invention.

FIG. 3 is a cross-sectional view of the square process tank implementing the system of the present invention taken along line III-III.

FIG. 4A is a process tank implementing the system of the present invention wherein a connecting structure is a curved surface.

FIG. 4B is a process tank implementing the system of the present invention wherein the connecting structure is a point of connection.

FIG. 5 is cross-section of a process tank implementing the system of the present invention illustrating filling and overflowing the process tank and the system of the present invention with liquid.

FIG. 6 is cross-section of a process tank implementing the system of the present invention illustrating draining the process tank and the system of the present invention.

## DETAILED DESCRIPTION OF THE DRAWINGS

FIG. 1 is an elevational view of a process tank 2 embodiment of the present invention having a particle barrier drain 3.

Referring to FIGS. 2 and 3, particle barrier drain 3 (FIG. 3) comprises an inner weir 4, an overflow wall 5, and a structure 6. In the illustrated embodiment, inner weir 4 is the top of the walls of process tank. However, the inner weir can be a separate component that fluidly connects to the walls of the process tank. Structure 6 connects overflow wall 5 and inner weir 4 so that drainage basin 7 is formed. In the preferred embodiment, structure 6 is a flat surface.

However, in alternate embodiments structure 6 can be a curved surface or merely a point of connection (FIGS. 4A and 4B).

Referring back to FIGS. 2 and 3, drain basin 7 has at least one drain hole. In the illustrated embodiment, a plurality of drain holes 8 are located on structure 6 and are spaced throughout the entirety of drainage basin 7. Overflow wall 5 has at least one recess 9 located near the top of overflow wall 5 and formed by peaks 26 of overflow wall 5. The <sup>recesses</sup> ~~recesses~~ 9 have bottoms 10. In the illustrated embodiment, overflow wall 5 has a plurality of saw-toothed recesses 9 located around the entire perimeter of overflow wall 5. However, recesses 9 can be any shape, for example rectangular, circular, or semi-circular.

Inner weir 4 has top surface 11. In order facilitate uniform overflow while preventing contaminants from reentering process tank 2, top surface 11 is just below the bottom 10 of the at least one recess 9. In the preferred embodiment, top surface 11 has inner edge 12 and outer edge 13, wherein top surface 11 is tapered downwardly from inside edge 12 to outside edge 13. In the preferred embodiment, inside edge 12 is just below the bottom 10 of the at least one recess 9.

Referring to FIG. 5, particle barrier drain 3 optionally comprises drain valve 14. Drain valve 14 is fluidly connected to the at least one drain hole 8. In those embodiments of the invention employing a plurality of drain holes 8, drain valve 14 is fluidly connected to each drain hole 8. Drain valve 14 has an open and closed position. Liquid can freely flow through the at least one drain hole 8 when drain valve 14 is opened. However, when drain valve 14 is closed, drain hole 8 is hermetically sealed, preventing any liquid from flowing through drain hole 8.

In operating the system according to the present invention, process tank 2 has a tank bottom 16. One or more wafer substrates 18 are placed in process tank 2. Liquid is supplied to process tank 2 by liquid supply 15 through supply opening 17 in tank bottom 16. Liquid is supplied until process tank 2 is filled and the liquid surface level is at position 20. Liquid supply



15 continues to supply liquid to process tank 2, causing spill over 21 of the liquid over inner weir

4. The liquid continues to be supplied, filling drainage basin 7 until the liquid surface level reaches position 22. In order to fill drainage basin 7, either drain valves 14 are closed or the liquid supply flow rate must be greater than the flow rate of liquid draining through drain holes

5 8. In the preferred embodiment, drain valves 14 are closed.

Once the liquid surface level is at position 22, liquid continues to be supplied to process tank 2, causing overflow 23 of the liquid over the over flow wall 5 through the at least one recess 9 (FIG. 4A). Because recesses 9 are located around the perimeter of overflow wall 5, overflow 23 is uniform over all sides of overflow wall 5. Overflow 23 through recesses 9 results in contaminants building up on peaks 26 of overflow wall 5.

Referring to FIG. 6, inner weir 4 prevents the contaminants that have built up on peaks 26 from reentering process tank 2 upon draining process tank 2. In draining the liquid according to the present invention, liquid supply 15 is discontinued. Once liquid supply 15 is discontinued, the liquid surface level stabilizes at position 22. At this point, in the preferred embodiment, drain valves 14 are opened. Once drain valves 14 are opened, the liquid drains through drain holes 8. The drain flow pattern 24 of the liquid is such that the liquid near overflow wall 5 which contains the built up contaminants drains through drain holes 8. Any contaminants that have built up near overflow wall 5 are prevented from flowing into process tank 2 by inner weir 4 which acts as a barrier as soon as it breaks through the lowering liquid surface. The liquid surface level eventually reaches and stabilizes at position 20 as a result of the liquid draining solely from drain holes 8. The remaining liquid is then drained from process tank 2 through tank drain 25. The system of the present invention can be used in any stage of integrated circuit processing in which a decrease in the number of contaminants that contact wafer 18 is desired. As such, process tank 2 can be a drying tank, a rinsing tank, or a chemical treatment tank.

While the invention has been described and illustrated in detail, various alternatives and modifications will become readily apparent to those skilled in the art without departing from the spirit and scope of the invention.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000